



ENGINE

| | |
|---------------------------------|-----------------|
| Make | Deutz F4L 1011F |
| Cylinders | 4 |
| Cooling system | air |
| Output at 2600 rpm (ISO 3046/1) | 40 kW (53.6 HP) |
| Electric starting | 12 V |

SPEED

| | |
|-------------------------------|------------|
| 1 st gear (work) | 0÷51 m/min |
| 2 nd gear (travel) | 0÷12 km/h |

SCREED RB 320

| | |
|--|-------------|
| Hydraulically extended screed width | 1.70÷3.20 m |
| with 2 extensions (0.20 m each) (optional) | max 3.60 m |
| with 4 extensions (0.20 m each) (optional) | max 4.00 m |
| Laying width reduction (optional) | 1.70÷0.65 m |
| Smoothing plate width | 265 mm |
| thickness | 10 mm |
| Heating | LPG |
| Smoothing plate vibration frequency | 0÷3400 rpm |
| | (0÷56.7 Hz) |

TECHNICAL SPECS

| | |
|-------------------------------------|----------------|
| Transmission | hydrostatic |
| Steering bogie wheels | 455 x 260 mm |
| No. 2 drive wheels | 365/80-R20 |
| Steering | power steering |
| Turning radius - inside | 3.00 m |
| outside | 5.20 m |
| Operating weight (CECE reg.) | 6300 kg |
| Hopper capacity (tunnel included) | 7.5 t |
| Hopper discharge height - at centre | 480 mm |
| at sides | 520 mm |
| Augers | Ø 260 mm |

PERFORMANCES

| | |
|----------------|----------|
| Max production | 120 t/h |
| Mat thickness | 5÷250 mm |

TANK CAPACITIES

| | |
|-------------------|------|
| Fuel | 70 l |
| Hydraulic oil | 63 l |
| Ecological liquid | 32 l |